

NISOS

With a maximum DLOR of 67%, **NISOS** is one of the most efficient downlights for its size on the market. In addition it's made from totally recyclable material, so good news for the environment. Single and twin lamp TCDE options range from 13W TCDE to 26W, whilst the 32W and 42W singles use TCTE lamps.

Two choices of reflector are offered, either matt or specular. The former has a speckled finish, which is extremely attractive when lit, and the latter conforms to the old LG3 Cat 2 standard.

A full range of dropped feature glasses are also offered together with an IP44 dished opal polycarbonate and a wall wash option.

The twist and lock bezel can be painted to any colour in the RAL range, please ask the sales office for further information.

Lamps are always supplied to ensure system compatibility.

Compact Fluorescent Recessed Downlights



NISOS with matt reflector



NISOS with specular reflector



NISOS with FGOE attachment



NISOS with wall wash

PART NUMBERS

Denotes NISOS range

Options: NI

NI

/

2

Denotes lamp wattage

Options:

13 = 13W TCDE

18 = 18W TCDE

26 = 26W TCDE

32 = 32W TCTE (1 lamp)

42 = 42W TCTE (1 lamp)

26

/

M

Denotes control gear type

Options:

DALI = DALI

ECO = Digital dimmable

HFR = 0-10V analogue dimmable

HF = High frequency

ECO

/

FGOE

Denotes emergency

Options:

EM = Remote maintained

EMST = As above with self test

Omit for non-emergency versions

EM

Denotes number of lamps

Options:

1 = 1 lamp

2 = 2 lamps

Denotes reflector type

Options:

S = Specular

M = Matt

Denotes attachment type

Options:

Omit for no attachment

FGOE = Feature glass outside etched

FGME = Feature glass middle etched

FGFE = Feature glass fully etched

FGC = Feature glass clear

FGEH = Feature glass etched, hole

FGCH = Feature glass clear, hole

IP44 = IP44 opal polycarbonate

WW = Wall wash attachment